

1 PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Blended Waxes, Inc.
1512 S. Main Street
P.O. Box 3044
Oshkosh, WI 54902

Contact: Lab
Phone: (920) 236-8080
Fax: (920) 236-8085
Web: www.blendedwaxes.com

Product Name: Bottle Sealing Wax
Revision Date: 7/31/2015
Version: 2
SDS Number: 022
Product Use: Used for sealing bottles

In case of emergency call:

Medical: 1-800-498-5701
Transportation (CHEMTREC): 1-800-424-9300
(24 hours/day, 7 days/week)

2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS):

NO GHS CLASSIFICATIONS INDICATED

GHS Label elements, including precautionary statements

GHS Signal Word: **NONE**

**NO GHS PICTOGRAMS INDICATED FOR
THIS PRODUCT**

GHS Hazard Statements:

NO GHS PRECAUTIONARY STATEMENTS INDICATED

GHS Precautionary Statements:

Hazards not otherwise classified (HNOC) or not covered by GHS

Route of Entry: Inhalation, Skin

Target Organs: NA

Inhalation: Fumes from molten material may cause mild respiratory irritation

Skin Contact: Product is minimally irritating to the skin upon contact. Contact with molten material may cause burns.

This material is not hazardous according to regulatory guidelines

Bottle Sealing Wax

SDS Number: 022

Revision Date: 7/31/2015

Page 2 of 4

3 COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas#	%	Chemical Name
8002-74-2		Paraffin wax fume
24937-78-8		Acetic acid ethenyl ester, polymer with ethene
63231-60-7		Paraffin waxes and Hydrocarbon waxes, microcryst.
9003-73-0		Cyclohexene, 1-methyl-4-(1-methylethenyl)-, homopolymer

4 FIRST AID MEASURES

- Inhalation:** Avoid inhalation of fumes. If symptoms develop, move victim to fresh air. If symptoms persist, seek medical attention.
- Skin Contact:** Wash contact areas with soap and water. If burned by contact with molten material, seek medical attention.
- Eye Contact:** Flush thoroughly with water. Seek medical attention
- Ingestion:** Product is non-toxic. Should stomach discomfort occur, seek medical attention

5 FIRE FIGHTING MEASURES

- Flash Point:** 430F
- Flash Point Method:** C.O.C.

Extinguishing Media: Dry chemical, CO2, foam or water fog. Treat as an oil fire, do not use stream of water

6 ACCIDENTAL RELEASE MEASURES

Dike or contain molten material. Allow material to solidify, then scrape up solid material. Handle as solid waste clean up. Clean up solid spills to prevent slippery surface conditions.

7 HANDLING AND STORAGE

- Handling Precautions:** When heated, the vapor/fumes given off may cause respiratory tract irritation. Handle with care and avoid spillage on the floor as it may create a slippery surface.
- Storage Requirements:** Store in cool, dry area away from heat or direct sunlight.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

- Engineering Controls:** TLV-TWA: 2/mg/m3 for fumes.
- Adequate ventilation to avoid build up of fumes.

- Personal Protective Equipment:** HMIS PP, B Goggles, Gloves

Additional protective clothing and/or equipment as required to prevent contact with molten wax.

Bottle Sealing Wax

SDS Number: 022

Revision Date: 7/31/2015

Page 3 of 4

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Variety of Colors
Physical State: Solid
Odor: Little to no odor
Freezing/Melting Pt.: 142F - 170F

10 STABILITY AND REACTIVITY

Stability: Product is stable under normal conditions
Conditions to Avoid: Avoid heating above 300 F to prevent build-up of fumes.
Materials to Avoid: Strong Oxidizing Agents
Hazardous Decomposition: Material does not decompose at ambient temperatures
Hazardous Polymerization: Will not occur

11 TOXICOLOGICAL INFORMATION

Product does not have any harmful effects based on available information.

12 ECOLOGICAL INFORMATION

We have no quantative data concerning the ecological effects of this product.

13 DISPOSAL CONSIDERATIONS

Observe all local, state and federal regulations.

14 TRANSPORT INFORMATION

Not a hazardous product according to DOT classifications

15

REGULATORY INFORMATION

Component (CAS#) [%] - CODES

Paraffin wax fume (8002-74-2) [n/a%] MASS, OSHAWAC, PA, TSCA, TXAIR

Acetic acid ethenyl ester, polymer with ethene (24937-78-8) [n/a%] TSCA

Paraffin waxes and Hydrocarbon waxes, microcryst. (63231-60-7) [n/a%] TSCA

Cyclohexene, 1-methyl-4-(1-methylethenyl)-, homopolymer (9003-73-0) [n/a%] TSCA

Regulatory CODE Descriptions

MASS = MA Massachusetts Hazardous Substances List

OSHA = OSHA Workplace Air Contaminants

PA = PA Right-To-Know List of Hazardous Substances

TSCA = Toxic Substances Control Act

TXAIR = TX Air Contaminants with Health Effects Screening Level

16

OTHER INFORMATION

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).